

Rustavi Steel LLC

12 Gagarini Str., 3700 Rustavi, Georgia

Tel.: +995 32 2 606699

+995 32 2 492233

Fax: +995 32 2 606699 (3030)

+995 32 2 492233 (3030)

contacts@rustavisteel.comwww.rmp.ge**Pipe Specifications According to API Spec 5 L Standard**

Pipe nominal sizes (mm) and weight (kg/m) according to API Spec 5L standards (ISO 4200)							
D outside diameter mm	T wall thickness mm						
	6.3	7.1	8	8.8	10	11	12.5
177.8	26.3	29.9	33.5	36.7	41.4	45.2	51.0
193.7	29.1	32.7	36.6	40.1	45.3	49.6	55.9
219.1	33.1	37.1	41.6	45.5	51.6	55.6	63.7
244.5		41.6	46.7	51.2	57.8	63.3	71.5
273		46.6	52.3	57.3	64.9	71.1	80.3
323.9		55.5	62.3	68.4	77.4	84.9	96.0
355.6				76.3	85.2	92.6	104.0
406.4				84.3	97.8	107.0	121.0

Steel grade for API Spec 5L (PSL 1): L210 or A; L245 or B; L290 or X42;

Pipe nominal sizes (mm) and weight (kg/m) according to API Spec 5L standards (sizes are indicated according to ASME B36.10M-2004)									
OD NPS in inches	T wall thickness in inches								
	8 (219,1mm)			0.322	0.344	0.375	0.406	0.438	0.5
			28.58	30.45	33.07	35.67	38.33	43.43	Weight
10 (273mm)		0.344	0.365	0.438	0.5				Wall Thickness
		38.27	40.52	48.28	54.79				Weight
12 (323,8mm)	0.330	0.344	0.375	0.406	0.438	0.5			Wall Thickness
	43.81	45.62	49.61	53.57	57.65	65.48			Weight
14 (355,6mm)		0.344	0.375	0.406	0.438	0.469	0.5		Wall Thickness
		50.22	54.62	59	63.5	67.84	72.16		Weight
16 (406,4mm)		0.344	0.375	0.406	0.438	0.469	0.5		Wall Thickness
		57.57	62.64	67.68	72.86	77.87	82.85		Weight

Steel grade for API Spec 5L (PSL 1): L210 or A; L245 or B; L290 or X42; L320 or X46.

Note: ASTM A106	Producing with Special tolerance +/-1% on outside diameter
	Rustavi Steel actual size range
	Sizes under implementation